+41 44 810 21 50 Tel +41 44 810 23 50 Fax: E-mail: info@geosig.com Web: www.geosig.com



GXX-3GUx Series 3G Modem

Features

- HSPA & Tri-Band GSM, upto 3.6 Mbps download
- USB interface
- Π High speed wireless network support
- Available as an internal module for GMSplus



GXX-3GUI internally mounted in GMSplus



GXX-3GUE used as external modem for GMSplus

Outline

The GXX-3GU series are 3G modems which provide a secure The 3G modem can be delivered either as an external module, wireless connection using the 3G network infrastructure for high speed data communications.

The GXX-3GU is a Multi-Band module solution with HSDPA as well as GSM/GPRS/EDGE with up to 3.6 Mbps for downlink data transfer.

connected to and powered directly from GMSplus series recorders or can be delivered as an internal module of GMSplus.

The unit is delivered with all necessary accessories, and peripheral units such as the cabling, connectors, antenna, etc as well as firmware & software, thus is ready to use out of the box together with the associated GeoSIG solution.

Specifications GXX-3GUx Series 3G Modem Functionality Power HSPA & Tri-Band GSM Powered directly from the GMSplus Bands 900/2100 MHz HSPA 850/900/1800 MHz GSM/GPRS/EDGE 56 mA standby Consumption 140 mA Peak Tx Output power HSPA Class 3 (0.25W) **Environment/Housing** GSM850/GSM900 Class 4 (2W) Dimensions GSM1800 Class 1 (1W) GXX-3GUI not applicable, inside GMSplus GXX-3GUE 80 mm x 160 mm x 60 mm SIM Card Supports 1.8 and 3 V SIM cards Mini SIM (25 mm x 15 mm) Weight GXX-3GUI not applicable, inside GMSplus GXX-3GUE approx. 300 g incl. cables Management **Environmental Protection** Configuration Through GMSplus GXX-3GUI same as GMSplus Data Transfer (maximum values) GXX-3GUE IP65 HSDPA 3.6 Mbps DL/UL EDGE/GPRS Multi-Slot Class 12 Temperature Data type used depends on telecommunication operator/provider and -30 to +80 °C Operation data transfer capacity in the chosen network. Storage -40 to +85 °C



